Navijin

DATASHEET

NETWORK INFRASTRUCTURE / **UNMANAGED POE SWITCH**

GET100-8P

8x 10G RJ45 Ports Unmanaged PoE Switch

PRODUCT PAGE

GET100-8P



160Gbps	119.04Mpps	110W
SWITCHING CAPACITY	PACKET FORWARDING RATE	POE POWER

Overview

8x 10G RJ45 Ports Unmanaged PoE Switch

Key Features

- 8x 100M/1000M/2.5G/5G/10G auto-sensing RJ45 ports
- 8x RJ45 ports support 802.3af/at(PoE+) standard
- Plug and play
- All ports have wire-speed forwarding capability

Hardware Specifications

Power Supply	AC 100-240V 50/60Hz
Protocol Standards	IEEE 802.3, 802.3u, 802.3ab, 802.3bz, 802.3x, 802.3cb, 802.3af, 802.3at
Ports	8x 100M/1000M/2.5G/5G/10G RJ45 ports
Indicator Light	8x Link/act indicators, 8x 10G speed indicators, Power
Network Medium	100Base-Tx: UTP/STP category 5, 5e cable (max. 100m) 1000Base-T: UTP/STP category 5e, 6 cable (max. 100m) 2.5GBase-T: UTP/STP category 5e, 6 cable (max. 100m) 5GBase-T: UTP/STP category 5e, 6 cable (max. 100m) 10GBase-T: UTP category 6cable (max. 55m), 7 cable (max. 100m)

Dimensions	291mm x 200mm x 45mm
PoE Port	8x IEEE 802.3at/af standard PoE ports
PoE Pin Definitions	1/2(+), 3/6(-)
PoE Power	110W
Total Power	150W
Forwarding Mechanism	Store-and-Forward
Switching Capacity	160Gbps
Packet Forwarding Rate	119.04Mpps
Jumbo Frame	12KBytes
MAC Address Table	16K
Environment	Operating Temperature: 0°C ~45°C Storage Temperature: -40°C ~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com** · **sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.