Navijin

DATASHEET

VIDEO SURVEILLANCE / **BULLET CAMERA**

ICA-N9074

MP mm IP67 50M-IR Metal IP Bullet 4 3.6 Body

PRODUCT PAGE

ICA-N9074



4MP	H.265	IP67
RESOLUTION	COMPRESSION	PROTECTION

Overview

The Navijin ICA-N9074 is an outdoor IP bullet camera for perimeter and facade surveillance – 4MP 3.6mm IP67 50M-IR Metal Body IP Bullet Camera. Key specifications include: Max. image resolution: 4MP(2560×1440); H.265 high effective compression, save bandwidth and storage space; IR distance can reach 50M. It is suited to car parks, building entrances, warehouses, fences and outdoor areas of hotels, schools and industrial sites, and works with Navijin NVRs and PoE switches for a complete surveillance system.

Key Features

- Max. image resolution: 4MP(2560 × 144)0
- H.265 high effective compression
- IR distance can reach 50M
- IP67 Metal body
- Support bidirectional talk

Camera

Image Sensor	1/2.8" Progressive scan 4 MP CMOS
Max. Resolution	4 MP(2560 × 1440)
Min. Illumination	0Lux(IR on); Color: 0.01Lux/F1.4; B/W:0.05Lux/F1.4

Shutter Time	1/25 to 1/10000s
Day/Night	Ext, Auto, Color, B/W; ICR
Lens Type	3.6 mm Prime lens
IR Distance	Smart IR; 50M (8x dual light leds)

Video and Audio

Video Encoding	Main stream: 2560 × 1440 @2 5 fps Sub-stream: D1(720x576), VGA(640x360)
Video Compression	H.264/H.265, 2 Stream
H.264 Encoding	BaseLine/Main Profile/High Profile
H.265 Encoding	Main Profile
Bit Rate Control	CBR, VBR (16kbps~8000kbps)
Region of Interest(ROI)	Support 4 zones, multi-stage level
Audio Compression	G.711u/G.711A
Audio Bit Rate	64Kbps

Network

Network Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTSP, RTMP, DDNS, UPnP, FTP
Interface Protocol	Onvif/SLINK/HTTP Push
Preview Monitoring	Mobile Phone/IMS/NVR/Browser
Simultaneous Live View	Up to 6-ch
User	User add/modify/delete, permission management
Security	Authorized user name and password, HTTPS encryption and AES link encryption, RTSP

Image

S/N Ratio	≥50db (AGC OFF)
Video Parameter	D-WDR/3D-NR/Defog
Day/Night Switch	Auto/Manual
Image Setting	Brightness, Contrast, Saturation, Sharpness, Hue
Privacy Mask	4 zones
OSD	Title, time and date overlay, multi-line OSD, OSD color optional

Event

Basic Event	Motion detection, Video tampering alarm, Human detection
Event Linkage	Snapshot, TF card video, FTP upload or Email sending, alarm output linkage, preset linkage

Interface

Ethernet Interface	1x RJ45 10M/100M network-adaptive Ethernet port
Audio	Built-in MIC

General

Power Supply	PoE (802.3at) / DC 12V
Power Consumption	≤7W
Material	Metal Body
Operating Temperature	-20°C ~ 55°C
Operating Humidity	0%-90%
Protection Grade	IP67

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com** · **sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.