Navijin

DATASHEET

VIDEO SURVEILLANCE / BULLET CAMERA

ICB-N2034

4MP, Human Detection Smart, Dual Light Bullet

PRODUCT PAGE

ICB-N2034



4MP	H.265	IP66	15M
RESOLUTION	COMPRESSION	PROTECTION	IR DISTANCE

Overview

4MP, Human Detection Smart, Dual Light Bullet Camera

Key Features

- Max. image resolution: 4MP(2560x1440)
- H.265 high effective compression
- IR distance can reach 15M
- IP66 Plastic casing
- Support bidirectional talk

Basic Parameter

Smart Function	Human detection
Image Sensor	1/2.7", 4MP progressive scan ultra-low illumination CMOS GC4653
Effective Pixels	4MP
Min. Illumination	Color: 0.1Lux@F1.2; B&W: 0Lux@F1.2(IR on)
Lens	F1.6 4mm
IR Distance	15M (4pcs dual light)

Noise Reduction	3D digital noise reduction
WDR	DWDR (Off/Low/Medium/High)
Mirror	Off/Horizontal mirroring/Vertical mirroring/180° rotation
Image Setting	Brightness/Contrast/Sharpness/Saturation/Chroma

Human Detection

Responding Speed	≤1s
Max. Detection Frame Rate	5fps/s (color image)
Detection Area	Support specified area, default full screen
Shielded Area	Support 4 areas setting
Upload Method	Private protocol upload
Trigger Method	Video trigger

Video and Audio Coding

Encoding Format	S265/H.265/H.264
Coding Characteristics	Main stream: 2592x1904@20fps, 2560x1440@25fps, 2304x1296@25fps, 1920x1080@25fps Sub-stream: D1(720x576), VGA(640x480), Q720P(640x360)
Video Bit Rate	Fixed bit rate, variable bit rate(1280kbps-4Mbps)
Video Type	Composite stream/Video stream
Audio Coding Standard	G.711U/64Kbps

Network

Ethernet Interface	1x RJ45 10M/100M self-adaptive Ethernet port
Network Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTSP, RTMP, DDNS, UPnP, NTP, SMTP
Interface Protocol	Onvif/SLINK
Preview Monitoring	Mobile Phone/IMS/NVR/Browser
Simultaneous Live View	Up to 2-ch
User	User add/Modify/Delete, permission management
Security	Authorized user name and password, HTTPS encryption and AES link encryption, RTSP

General

Power Supply	PoE (802.3at) / DC 12V
Power Consumption	≤10W
Dimensions(mm)	58.47mm x 58.47mm x 183.74mm
Operating Temperature	-20°C ~ 55°C
Operating Humidity	0%-90%

Protection Grade	IP66
Weight	350g

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com** · **sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.