Navijin

DATASHEET

VIDEO SURVEILLANCE / **BULLET CAMERA**

ICB-N7095

5MP Dual Light Human Detection IP Bullet Camera

PRODUCT PAGE

ICB-N7095



5MP	H.265	IP66	8 pcs IR leds
RESOLUTION	COMPRESSION	PROTECTION	IR DISTANCE

Overview

The Navijin ICB-N7095 is an outdoor IP bullet camera for perimeter and facade surveillance – 5MP Dual Light Human Detection IP Bullet Camera. Key specifications include: Max. image resolution: 5MP(2592x1904); H.265 high effective compression; IR distance can reach 30M. It is suited to car parks, building entrances, warehouses, fences and outdoor areas of hotels, schools and industrial sites, and works with Navijin NVRs and PoE switches for a complete surveillance system.

Key Features

- Max. image resolution: 5MP(2592x1904)
- H.265 high effective compression
- IR distance can reach 30M
- IP66 Metal + Plastic casing
- Support bidirectional talk

Camera

Image Sensor	1/2.8", 5MP low illumination CMOS sensor
Max. Resolution	5MP(2592x1904)
Min. Illumination	0Lux/F1.4(IR on), Color: 0.1Lux/F1.4 B/W: 0.05Lux/F1.4
Shutter Time	1/25 to 1/10000s

Day/Night	ICR switch, auto, color, B/W, ext.
Lens Type	2.8 – 12mm lens
IR Distance	8 pcs IR leds, IR distance 30M

Video and Audio

Video Encoding	Main stream: 2592x1904@25fps Sub-stream: Sub-stream: D1(720x576), VGA(640x480), Q720P(640x360), CIF(352x288)
Video Compression	H.265+/H.265/H.264
H.264 Encoding	BaseLine/Main Profile/High Profile
H.265 Encoding	Main Profile
Bit Rate Control	CBR, VBR (16kbps~8000kbps)
Region of Interest(ROI)	Support 4 zones, multi-stage level
Audio Compression	G.711u/G.711A
Audio Bit Rate	64Kbps

Network

Network Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTSP, RTMP, DDNS, UPnP, NTP, SMTP
Interface Protocol	Onvif/SLINK
Preview Monitoring	Mobile Phone/IMS/NVR/Browser
Simultaneous Live View	Up to 6-ch
User	User add/modify/delete, permission management
Security	Authorized user name and password, HTTPS encryption and AES link encryption, RTSP

Image

S/N Ratio	≥35db (AGC OFF)
Video Parameter	D-WDR/3D-NR/Defog
Day/Night Switch	Auto/Manual
Image Setting	Brightness, Contrast, Saturation, Sharpness, Hue
Privacy Mask	4 zones
OSD	Title, time and date overlay, multi-line OSD, OSD color optional

Event

Basic Event	Motion detection, Video tampering alarm, Human detection
Event Linkage	Snapshot, TF card video, FTP upload or Email sending, alarm output linkage, preset linkage

Interface

Ethernet Interface	1x RJ45 10M/100M network-adaptive Ethernet port

Audio	Built-in MIC

General

Power Supply	PoE (802.3at) / DC 12V
Power Consumption	≤9W
Material	Metal + Plastic
Operating Temperature	-10°C ~ 50°C
Operating Humidity	0%-90%
Protection Grade	IP66

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com · sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.